



Poli-Flex

**Poli-Flex® Image, Poli-Flex
4280/4281/4282 // PT450**

Art.-Nr.: PT450

- Technical data: Transfer film: Polyurethane design film / Adhesive: Polyurethane-hotmelt / Thickness [mm]: 0.090 +/- 10% (Camouflage); 0.090 +/- 10% (Leopard); 0.090 +/- 10% (Zebra) / Liner: PET film, self-adhesive
- Transfer Conditions: Temperature: 160 °C / Pressure: 2,5 - 3,0 bar [medium pressure] / Time: 15 sec.
- Wash resistance: 60 °C / Wash textile inside out / Tumble dryable
- POLI-FLEX® IMAGE are transfer films with a fashionable design and unique surface finish. The environmentally friendly polyurethane film offers excellent resistance to washing and cleaning and is pleasant to the touch. POLI-FLEX® IMAGE is suitable to transfer onto textiles like cotton, mixtures of polyester/cotton and polyester/acrylic
- POLI-FLEX® IMAGE can be cut with all current plotters. We recommend using a standard blade (45°). After weeding the cut flex film is transferred by heat press
- The PET liner of all POLI-FLEX® IMAGE (4280 - 4282) products should be removed warm
- Nylon and textiles with hydrophobic impregnation are not suitable for heat transfer. In this case, L-Flex Nylon T500 should be used.
- We recommend carrying out an application test on original

materials.

- Due to the various influences resulting from the production and transfer of the transfer film, the nature of the materials and the washing and cleaning conditions, product liability can only apply to unprocessed materials.