



Poli-Flex

**Poli-Flex® Image 4212/4213,
Poli-Flex 4212/4213 // PT453**

Art.-Nr.: PT453

- Technical data: Transfer film:
Polyurethane design film / Turbo
Reflex: Effect film / Adhesive:
Polyurethane-hotmelt /
Thickness [mm]: 0.055 +/- 10%
(Gold); 0.055 +/- 10% (Silver) /
Liner: PET film, self-adhesive
- Transfer Conditions:
Temperature: 160 °C / Pressure:
2,5 - 3,0 bar [medium pressure]
/ Time: 15 sec. (3 sec. post-
pressing)
- Wash resistance: 40 °C /
Suitable for tumble dry / Wash
textile inside out
- POLI-FLEX® IMAGE are
transfer films with a fashionable
design and unique surface
finish. The environmentally
friendly polyurethane film offers
excellent resistance to washing
and cleaning and is pleasant to
the touch. POLI-FLEX® IMAGE is
suitable to transfer onto textiles
like cotton, mixtures of
polyester/cotton and
polyester/acrylic
- POLI-FLEX® IMAGE can be cut
with all current plotters. We
recommend using a standard
blade (45°). After weeding the
cut flex film is transferred by
heat press
- The PET liner of POLI-FLEX®
GOLD and SILVER (4212-4213)
should be removed after cooling
down
- Nylon and textiles with
hydrophobic impregnation are
not suitable for heat transfer. In
this case, L-Flex Nylon T500
should be used.
- We recommend carrying out
an application test on original

materials.

- Due to the various influences resulting from the production and transfer of the transfer film, the nature of the materials and the washing and cleaning conditions, product liability can only apply to unprocessed materials.