



Poli-Flex

**Ultimate Print Supersoft
4033 Matt, Poli-Flex 4033 //
PT904**

Art.-Nr.: PT904

- Technical Data: Transfer Film: Polyurethane, cast
- Adhesive: Polyurethane-hotmelt
- Thickness [mm]: 0,05 +/- 5 %
- (Standard)Liner: PET-film, non adhesive
- Transfer Conditions: Temperature: 160 °C
- Pressure: 2.5-3.0 bar [average pressure]
- Time: 15 sec.
- Wash resistance: 40 °C
- Only use colour or mild detergent
- Wash textile inside out
- Suitable for tumble drying
- Printing: True sided
- ULTIMATE PRINT SUPERSOFT 4033 MATT is a heat-sealable, printable PU textile transfer film (opaque white, 50 ?) suitable for light and dark textiles
- Due to a special top coat, the film offers an excellent washing-resistance
- ULTIMATE PRINT SUPERSOFT 4033 MATT offers a high print resolution with a semi-matt finish and has a pleasant soft textile touch
- ULTIMATE PRINT SUPERSOFT 4033 MATT is compatible with all current printers using ECO-solvent, solvent and latex inks
- Due to a newly developed, non-adhesive PET film liner, even very small letters and motifs can be easily cut by all current CAD/CAM plotters after the printing process
- We recommend the use of POLI-TACK 854 + 870 for

transfer and as a protective cover during hot transfer

- The PET liner should be removed warm
- The transfer film is used for motifs and logos on sport, leisure and work wear
- Fabrics that have a water-repellent finish or waterproofing are not suitable for heat transfers
- The raw materials used are not harmful to the environment and are free from PVC, plasticisers and heavy metals (Standard 100 by Oeko-Tex)
- We recommend to carry out an application test on original materials
- Due to the various influences resulting from the production and transfer of the transfer film, the nature of the materials and the washing and cleaning conditions, product liability can only apply to unprocessed materials.