



Poli-Tape Flock

Solvent-Flock 5905, Poli-Tape Flock 5905 // PT950

Art.-Nr.: PT950

- Technical Data: Transfer Film: Viscose Flock
- Adhesive: Copolyester-hotmelt
- Thickness in [mm]: 0.56 +/- 5%
- (Standard)Liner: Silicone-paper, white
- Transfer Conditions: Temperature: 160 °C
- Pressure: 2.5-3.0 bar [average pressure]
- Time: 15 sec.
- Wash resistance: 40 °C
- Only use colour or mild detergent
- Wash textile inside out
- Suitable for tumble drying
- SOLVENT-FLOCK 5905 is a heat-sealable Viscose Flock (white, 560 ?) which is suitable for direct printing with Eco-Solvent and solvent inks
- Due to the special fiber impregnation, a photo-realistic print resolution with radiant colours is achieved
- The liner on the hotmelt side allows motifs and logos to be cut by all current CAD/CAM plotters after printing
- The Flock has excellent cutting and weeding abilities and convinces due to excellent washing resistance
- SOLVENT-FLOCK 5905 is used for motifs and logos on sport, leisure and work wear
- Fabrics that have a water-repellent finish or waterproofing are not suitable for heat transfers
- We recommend to carry out an application test on original materials

-
- Due to the various influences resulting from the production and transfer of the transfer film, the nature of the materials and the washing and cleaning conditions, product liability can only apply to unprocessed materials.